Example: INH-10-1-R-BA-MB







## IRONCLAD® ZERO-WATT

## **INH Series Exit Signs**

The Ironclad® Zero-Watt INH series provides rugged cast aluminum heavy duty frames with a 3/8" polycarbonate lens for more demanding correctional and institutional applications. As the name implies, this maintenance-free fixture is self-sustaining and runs up to 20 years with no batteries, no wiring, and zero electricity. Zero-Watt is recyclable at the end of it's useful life.

## **Ordering Chart Information**

Model	Service Life		No. Of Faces		Face Color		Frame Color		Options
INH	10	10 Years	1	Single Face	R	Red	ВА	Brushed Aluminum	MB Mounting Bracket for Single or Double Face
	20	20 Years - 1/8" Polycarbonate	2	Double Face	G	Green	В	Black	
					В	Black	W	White	Signs

For accessories not shown or custom plates, please contact customer service at (800) 223-0853.

### **Specifications**

#### CONSTRUCTION

- Heavy-duty cast aluminum frame offered in single and double face (mounting bracket included with double face sign)
- 6" high letters with 3/4" stroke available with Red, Green, or Black faceplate suitable for use in hazardous atmospheres and damp locations.
   Meets NEC Article 500, Class 1, 11 and 111 conditions
- Beveled edges and rounded corners withstand high impacts
- · Tamper proof mounting hardware prevents unauthorized removal
- Standard exterior finish, brushed aluminum with clear lacquer coating.
   Custom paint or anodized colors available
- Aluminum stencil face with field selectable chevron directional indicators
- 3/8" clear Polycarbonate shield seals lamp compartment and prismatic refractor lens
- Operating temperature -55°C to 80°C
- Available in service life ratings of 10 or 20 years

#### **POWER SOURCE**

- Non-electrical, internally illuminated by sealed tritium gas light sources
- Requires no external light source, electrical power, wiring or batteries 100% reliable, maintenance free and always on

#### **ILLUMINATION**

 Green light output for maximum visibility in emergency conditions 100 foot visibility rating

#### **CERTIFICATION**

 Tested, approved and listed by Underwriters Laboratories to UL 924, and meets NFPA101 Life Safety Code

#### WARRANTY

Limited warranty for the rated life of the product

## **Dimensional Data**

# 1.87" | 12.25" | 16.75"

## 12.25"

**Ceiling Mount** 

